

CHILLERS, FREEZERS & COMBINATION

(Two, Four and Six Door)



RS- R1004

FEATURES

- | Adjustable Thermostat
- | Timer Defrost Function
- | 60 mm PU Insulation
- | Heavy Duty Castor
- | Danfoss Compressor
- | Digital Thermometer
- | Adjustable Shelvings
- | Auto Closing Door

UNIT: mm



MODEL	DESCRIPTION	REFRIGERANT	VOLUME	TEMPERATURE	POWER CONSUMPTION
RS-R1002C	TWO DOOR 4 SHELVES	R134A	550L	+1°C ~ +4°C	260W
RS-R1002F		R404A	550L	0°C ~ -20°C	400W
RS-R1002CB		R404A	550L	-20°C / +1°C ~ +4°C	260W
RS-R1004C	FOUR DOOR 8 SHELVES	R134A	890L	+1°C ~ +4°C	400W
RS-R1004F		R404A	890L	0°C ~ -20°C	750W
RS-R1004CB		R404A	890L	-20°C / +1°C ~ +4°C	400W
RS-R1006C	SIX DOOR 12 SHELVES	R134A	1400L	+1°C ~ +4°C	600W
RS-R1006F		R404A	1400L	0°C ~ -20°C	1100W
RS-R1006CB		R404A	1400L	-20°C / +1°C ~ +4°C	750W